

## Turbo separator

Item no. 33744


The compact CBMS 20 turbo separator guarantees economical and resource-saving operation of the wet blasting system.




## Specifications

Process step	<b>radiate</b> <b>Finishing</b>
Coating procedure	<b>Pretreatment</b> <b>Follow up treatment</b>
Type	<b>CBMS 20</b>
Net weight	<b>270 kg</b>
measurement (LxWxH)	<b>Dimensions plant: 550 x 800 x 1700 mm</b> <b>min. footprint: 1000 x 1000 mm</b>
Connected Load (KW)	<b>2,7</b>
Ampere	<b>25 A</b>

Contact experts

 +49 2405 44 70 122

 [coatingtechnology@cemecon.de](mailto:coatingtechnology@cemecon.de)

A constantly high blasting medium quality is guaranteed by the use of the separator. It separates the used blasting medium (e.g. high-grade corundum) from the blasting liquid in order to maintain the blasting quality at a constantly high level through targeted refilling of new blasting medium. In conjunction with the blast machine, the Turbo Separator operates almost fully automatically. It is installed near the blast machine. From the wet blasting system, the blasting liquid runs together with the blasting medium into the separator. There, the used blasting medium is separated. Refilling of the used blasting medium can be done quickly and accurately.

The UL standards are product safety standards for the US market developed by Underwriters Laboratories (UL).